

Product datasheet

Specifications



current transformer TI 400/5 A - for Linergy bar 800 to 1600 A

16479

ⓘ Discontinued on: 17 November 2014

ⓘ Discontinued

Main

Range	PowerLogic
Product name	CT
Product or component type	Current transformer
Secondary current	5 A
Accuracy class	Class 0.5 at 4 VA Class 1 at 8 VA Class 3 at 10 VA
[In] rated current	400 A

Complementary

Current transformer type	Tropicalised for busbar
Current transformer ratio	400/5
Maximum safety factor	5
[Ue] rated operational voltage	< 720 V AC 50/60 Hz
Mounting mode	Insulated locking screw
Mounting support	Busbar
Width	32 mm inner: 90 mm outside:
Height	65 mm inner: 90 mm outside:
Depth	87 mm outside:
Net weight	0.6 kg
Opening of bars	65 x 32
Sealing	With

Environment

Standards	IEC 60044-1 VDE 0414
Product certifications	CE
IP degree of protection	IP20
Relative humidity	95...100 %

Ambient air temperature for operation -25...60 °C

Contractual warranty

Warranty 18 months

Recommended replacement(s)

16479 is replaced by:

1x



current transformer tropicalised 400 5 double output for bars 32x65
METSECT5DA040
