

SPD01-4P



SPD02




SPD01-1P




SPD03


► SPD01/02-1P





► SPD03-1P



► SPD01/02-4P



► SPD03-4P



MOV varistor

galvanised
steel terminalterminal capacity:
max. 35mm²possibility to connect
with comb rails

DIN35 rail mounting



replaceable inserts *

green protector status
indicator light – insert
in working order
red – to be replaced

Schelinger



EAN



package



class

U_p
voltage protection
level [kV]

I_{imp}
(10/350 μ s)
inrush current
[kA]

I_n
(8/20 μ s)
rated discharge
current [kA]

I_{max}
(8/20 μ s)
limit discharge
current [kA]

code	EAN	package	class	voltage protection level [kV]	inrush current [kA]	rated discharge current [kA]	limit discharge current [kA]
A51-SPD01-1P-C	5900280964533	1/144	C / T2	≤ 1.5	-	20	40
A51-SPD01-4P-C	5900280964540	1/36	C / T2	≤ 1.5	-	20	40
A51-SPD01-1P-B+C	5900280916631	1/144	B+C / T1+T2	≤ 1.5	5	20	50
A51-SPD01-4P-B+C	5900280916648	1/36	B+C / T1+T2	≤ 1.5	5	20	50
A51-SPD02-1P-B+C	5900280964571	1/144	B+C / T1+T2	≤ 1.5	8	20	50
A51-SPD02-4P-B+C	5900280958143	1/36	B+C / T1+T2	≤ 1.5	8	20	50
A51-SPD03-1P-B+C	5900280964557	1/144	B+C / T1+T2	≤ 2.0	12.5	20	50
A51-SPD03-4P-B+C	5900280964564	1/36	B+C / T1+T2	≤ 2.0	12.5	20	50

* Replaceable inserts available from Schelinger