

Product datasheet

Specifications



current transformer TI 200/5 A - for cable Ø 21 mm

16456

! Discontinued on: 17 November 2014

! Discontinued

Main

Range	PowerLogic
Product name	CT
Product or component type	Current transformer
Secondary current	5 A
Accuracy class	Class 0.5 at 4 VA Class 3 at 6 VA Class 1 at 5.5 VA
[In] rated current	200 A

Complementary

Current transformer type	Tropicalised for cable
Current transformer ratio	200/5
Maximum safety factor	5
[Ue] rated operational voltage	< 720 V AC 50/60 Hz
Mounting support	Mounting plate DIN rail
Width	44 mm outside:
Height	65 mm outside:
Depth	30 mm outside:
Diameter	21 mm
Net weight	0.2 kg
Cable outer diameter	21 mm - cable 0...120 mm ²
Sealing	With

Environment

Standards	IEC 60044-1 VDE 0414
Product certifications	CE
IP degree of protection	IP20
Relative humidity	95...100 %

Ambient air temperature for operation -25...60 °C

Offer Sustainability

EU RoHS Directive [Compliant](#)
[EU RoHS Declaration](#)

China RoHS Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Contractual warranty

Warranty 18 months

Recommended replacement(s)

16456 is replaced by:

1x



current transformer tropicalised DIN mount 200 5 for cables d. 21
METSECT5CC020